



PRUNER BIOIL - FILTER

OIL, GREASE, BTEX AND TPH REMOVAL

Maximizing Efficiency <> Enquadrando Lançamento

Pruner Bio Oil Filter acts like filter, pre-treatment or post-treatment in:

- ➔ In Situ Decontamination
- ➔ Wood Treatment
- ➔ Spare Parts Cleaning
- ➔ Gas Stations
- ➔ Wheel Cleaners
- ➔ Water-Oil Separators
- ➔ Mechanic Industries
- ➔ Industries in General

Resulting in:

- ➔ Oil removal at 4 ppm
- ➔ Benzeno removal at 9.88 ppb
- ➔ Reduction of Total Xilenos at 9.23 ppb



Pruner Bio-Oil Filter is a percolation / adsorção system of water treatment through mechanical removal and chemical adsorção. Pruner Bioil removes emulsificados oils and greases, free oils and organic molecules of high molecule weight, gasoline, diesel, organic pigments, acids, pentaclorofenol and hidrocarboneto.

Pruner Bio-Oil is highly versatile and effective and can be used as pre-treatment, post-treatment or as a single process. At the end, Pruner Bioil percolation means can be incinerated in cement furnace generating 10.000 kcal/kg or taken to embankments according to the classification of filtered compounds.

PRUNER ENVIRONMENTAL TECHNOLOGY – PHONE 31-3581-2876 <>3547-2381
pruner@pruner.com.br